EVE-RESS: HVI-20.0, HVI-40.0, HVI-60.0

	Item		Specifications	EVE-HVI-20.0	EVE-HVI-40.0	EVE-HVI-60.0
Pack			Battery module		1P16S	
- G-G-K			Rated energy	5.12kWh		
	EVE Energy	COM1	Rated voltage	51.2V		
B+ B-			Weight	41kg		
3			Dimension (H * W * D)	420*442*131mm		
System Netwy Netwy Netwy Netwy	CMEEningy CMEEningy	Rated energy	20.48kWh	40.96kWh	61.44kWh	
		Number of Packs	4	8	12	
		(gmd3/4)	Max. constant charge and discharge current	100A		
			Rated voltage	204.8V	409.6V	614.4V
			*Rated capacity	100Ah		
			Weight (without rack)	177kg	341kg	505kg
			DOD	90%		
			Communication	CAN		
			Humidity	≤70% (no condensation)		
			IP rating	IP20		
			Cycle life	≥5000次 (according to standard test condition)		
			Certification	UN38.3,CE, IEC62619 (Available), UL1973,UL9540A (design to meet)		
HVI-20.0	HVI-40.0	HVI-60.0				00v DOD 6 - 6 - 1 1 - v 25 1200

^{*} Rated capacity: 100% DOD for fresh battery, 25±2°C, 0.5°C. * Max. 12packs in series (61.44kWh)